Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-503-7085

## Section Quantity:

1

Body Style:

Cylindrical bushing mounted

# **Reliability Indicator:**

Not established

### **Overall Length:**

1.125 inches

#### Body Diameter:

1.125 inches

Shaft Diameter:

0.250 inches

Shaft Length:

0.625 inches

### Mounting Bushing Length:

## 0.500 inches

**Body Length:** 

0.500 inches

Shaft Style:

Round, slotted

Shaft Bearing Type:

Bearing

#### Actuator Type:

Single shaft

#### Nonturn Device Location:

At 9 oclock

**Nonturn Device Radius:** 

0.531 inches

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

**Mounting Method:** 

Locking bushing

#### **Electrical Resistance Per Section:**

250.000 ohms single section

## Power Dissipation Rating Per Section In Watts:

2.0 free air single section

### **Function Conformity Per Section:**

Single section independent linearity



**Resistance Tolerance Per Section In Percent:** 

-10.0 to 10.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0