Nonprecision Wire Wound Variable Resistor - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5905-00-503-7999

Section Quantity: 1 **Body Style:** Rectangular w/mounting holes **Reliability Indicator:** Not established **Terminal Length:** 0.172 inches Mounting Hole Diameter: Between 0.075 inches and 0.081 inches Shaft Diameter: Between 0.055 inches and 0.085 inches Shaft Length: 0.045 inches **Body Length:** Between 0.490 inches and 0.510 inches **Body Width:** Between 0.210 inches and 0.230 inches **Body Height:** Between 0.490 inches and 0.510 inches Shaft Style: Round, slotted Actuator Type: Single shaft Effective Electrical Rotation In Deg Angular Rotation: 9000.0 Maximum Starting Torque: 5.00 inch-ounces Maximum Running Torque: 5.00 inch-ounces **Center To Center Distance Between Terminals:** 0.200 inches Lateral Distance Between Mounting Hole Centers: 0.520 inches **Mounting Facility Quantity:** 2 **Terminal Location:** Rear end **Mounting Method:** Unthreaded hole **Electrical Resistance Per Section:** 50.0 kilohms single section

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Rotary Actuator Travel In Angular Deg:

9000.0

Center To Center Distance Between Center Terminal And Outside Terminal:

0.100 inches

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

Power Dissipation Rating Per Section In Watts:

1.0 free air single section

Resistance Tolerance Per Section In Percent:

-5.0/+5.0 single section

Actuator Travel Control Feature:

Clutch

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Terminal Type And Quantity:

3 pin

Specification Data:

83298-819798 manufacturers source control

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Deminitarizatio

No

Fiig:

A002a0