## NSN 5905-00-503-9009

Film Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-503-9009

Tempurature Coefficient Of Resistance in Ppm Per Deg Celsius: -1.00.0/+100.0   -1.00.0/+100.0   -1.00.0/+100.0   -1.00.0/+100.0   -1.00.0/+100.0   -1.00.0/+100.0   -1.00.0   -1	
Electrical Resistance: 1.100 kilohms Resistance Tolerance in Percent: -2.000/+2.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level in Percent: 0.010 Terminal Length: 1.250 inches Body Diameter: 0.066 inches Body Diameter: 0.150 inches Power Dissipation Rating in Watts: 0.125 free air Unpackaged Unit Weight: 0.300 grams Style Designator:	
1.100 kilohms  Resistance Tolerance In Percent: -2.000/+2.000  Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0  Inclosure Method: Encapsulated  Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010  Terminal Length: 1.250 inches Body Diameter: 0.056 inches Body Length: 0.150 inches Power Dissipation Rating In Watts: 0.125 free air Unpackaged Unit Welght: 0.300 grams Style Designator:	
Resistance Tolerance In Percent: -2.000/+2.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 155.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: 1.250 inches Body Diameter: 0.066 inches Body Length: 0.150 inches Power Dissipation Rating In Watts: 0.125 free air Unpackaged Unit Weight: 0.300 grams Style Designator:	
Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: 1.250 inches Body Diameter: 0.066 inches Body Length: 0.150 inches Power Dissipation Rating In Watts: 0.125 free air Unpackaged Unit Weight: 0.300 grams Style Designator:	
Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: 1.250 inches Body Diameter: 0.066 inches Body Length: 0.150 inches Power Dissipation Rating In Watts: 0.125 free air Unpackaged Unit Weight: 0.300 grams Style Designator:	
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0  Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010  Terminal Length: 1.250 inches Body Diameter: 0.066 inches Body Length: 0.150 inches Power Dissipation Rating In Watts: 0.125 free air Unpackaged Unit Weight: 0.300 grams Style Designator:	
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0  Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010  Terminal Length: 1.250 inches Body Diameter: 0.066 inches Body Length: 0.150 inches Power Dissipation Rating In Watts: 0.125 free air Unpackaged Unit Weight: 0.300 grams Style Designator:	
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: 1.250 inches Body Diameter: 0.066 inches Body Length: 0.150 inches Power Dissipation Rating In Watts: 0.125 free air Unpackaged Unit Weight: 0.300 grams Style Designator:	
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: 1.250 inches Body Diameter: 0.066 inches Body Length: 0.150 inches Power Dissipation Rating In Watts: 0.125 free air Unpackaged Unit Weight: 0.300 grams Style Designator:	bient Tempurature In Deg Celsius At Zero Percent Rated Power:
-55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: 1.250 inches Body Diameter: 0.066 inches Body Length: 0.150 inches Power Dissipation Rating In Watts: 0.125 free air Unpackaged Unit Weight: 0.300 grams Style Designator:	.0
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: 1.250 inches Body Diameter: 0.066 inches Body Length: 0.150 inches Power Dissipation Rating In Watts: 0.125 free air Unpackaged Unit Weight: 0.300 grams Style Designator:	npurature Range Of Tempurature Coefficient In Deg Celsius:
Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: 1.250 inches Body Diameter: 0.066 inches Body Length: 0.150 inches Power Dissipation Rating In Watts: 0.125 free air Unpackaged Unit Weight: 0.300 grams Style Designator:	0/+150.0
Terminal Type:  Wire lead  Reliability Indicator:  Established  Reliability Failure Rate Level In Percent:  0.010  Terminal Length: 1.250 inches  Body Diameter: 0.066 inches  Body Length: 0.150 inches  Power Dissipation Rating In Watts: 0.125 free air  Unpackaged Unit Weight: 0.300 grams  Style Designator:	osure Method:
Wire lead  Reliability Indicator: Established  Reliability Failure Rate Level In Percent: 0.010  Terminal Length: 1.250 inches  Body Diameter: 0.066 inches  Body Length: 0.150 inches  Power Dissipation Rating In Watts: 0.125 free air  Unpackaged Unit Weight: 0.300 grams  Style Designator:	apsulated
Reliability Indicator: Established  Reliability Failure Rate Level In Percent: 0.010  Terminal Length: 1.250 inches  Body Diameter: 0.066 inches  Body Length: 0.150 inches  Power Dissipation Rating In Watts: 0.125 free air  Unpackaged Unit Weight: 0.300 grams  Style Designator:	minal Type:
Established  Reliability Failure Rate Level In Percent:  0.010  Terminal Length: 1.250 inches  Body Diameter: 0.066 inches  Body Length: 0.150 inches  Power Dissipation Rating In Watts: 0.125 free air  Unpackaged Unit Weight: 0.300 grams  Style Designator:	e lead
Reliability Failure Rate Level In Percent:  0.010  Terminal Length:  1.250 inches  Body Diameter:  0.066 inches  Body Length:  0.150 inches  Power Dissipation Rating In Watts:  0.125 free air  Unpackaged Unit Weight:  0.300 grams  Style Designator:	iability Indicator:
Terminal Length: 1.250 inches  Body Diameter: 0.066 inches  Body Length: 0.150 inches  Power Dissipation Rating In Watts: 0.125 free air  Unpackaged Unit Weight: 0.300 grams  Style Designator:	ablished
Terminal Length:  1.250 inches  Body Diameter:  0.066 inches  Body Length:  0.150 inches  Power Dissipation Rating In Watts:  0.125 free air  Unpackaged Unit Weight:  0.300 grams  Style Designator:	iability Failure Rate Level In Percent:
1.250 inches  Body Diameter: 0.066 inches  Body Length: 0.150 inches  Power Dissipation Rating In Watts: 0.125 free air  Unpackaged Unit Weight: 0.300 grams  Style Designator:	10
Body Diameter:  0.066 inches  Body Length:  0.150 inches  Power Dissipation Rating In Watts:  0.125 free air  Unpackaged Unit Weight:  0.300 grams  Style Designator:	minal Length:
0.066 inches  Body Length: 0.150 inches  Power Dissipation Rating In Watts: 0.125 free air  Unpackaged Unit Weight: 0.300 grams  Style Designator:	50 inches
Body Length:  0.150 inches  Power Dissipation Rating In Watts:  0.125 free air  Unpackaged Unit Weight:  0.300 grams  Style Designator:	dy Diameter:
0.150 inches  Power Dissipation Rating In Watts: 0.125 free air  Unpackaged Unit Weight: 0.300 grams  Style Designator:	66 inches
Power Dissipation Rating In Watts:  0.125 free air  Unpackaged Unit Weight:  0.300 grams  Style Designator:	dy Length:
0.125 free air  Unpackaged Unit Weight:  0.300 grams  Style Designator:	50 inches
Unpackaged Unit Weight: 0.300 grams Style Designator:	ver Dissipation Rating In Watts:
0.300 grams Style Designator:	25 free air
Style Designator:	packaged Unit Weight:
•	00 grams
Axial terminal each end	le Designator:
	al terminal each end
Test Data Document:	t Data Document:
81349-mil-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification	49-mil-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	nat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	ironmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:	ecification Data:
81349-mil-r-39017/5 government specification	49-mil-r-39017/5 government specification
Shelf Life:	
N/a	
Unit Of Measure:	

No

Demilitarization:

## NSN 5905-00-503-9009

Film Fixed Resistor - Page 2 of 2



Fiig:

A001a0