NSN 5905-00-504-4655

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-504-4655

-100.0/+100.0 Ellectrical Resistance: 2.610 kilolms Resistance Tolerance in Percent: -1.000/+1.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -25.0/+125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: -1.550 inches Body Diameter: 0.102 inches Body Length: 0.250 inches Power Dissipation Rating in Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 18338-123382 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Na Unit of Measure:	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
2.610 kilohms Resistance Tolerance in Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -25.0/+125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.550 inches Body Diameter: 0.102 inches Body Diameter: 0.102 inches Rody Langth: 0.250 inches Power Dissipation Rating In Watts: 0.125 fee air Style Designator: Assial terminal each end Test Data Document: 18338-123362 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) No Unit Of Measure: Demilitarization: No Filig:	-100.0/+100.0
Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 7.0.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -25.0/+125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Note established Terminal Length: 1.550 inches Body Diameter: 0.102 inches Body Jength: 0.250 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Avial terminal each end Test Data Document: 18338-123362 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Sheft Life: Na Unit Of Measure:	Electrical Resistance:
-1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -25.0/+125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.550 inches Body Diameter: 0.102 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Avial terminal each end Test Data Document: 18338-123362 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Na Unit Of Measure:	2.610 kilohms
Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -25.0/+125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.550 inches Body Diameter: 0.102 inches Body Diameter: 0.102 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Stal terminal each end Test Stal Source (Insist is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Sheft Life: No Unit Of Measure: - Demilitarization: No Filig:	Resistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -25.0/+125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.550 inches Body Diameter: 0.102 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 18338-123382 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Na Unit Of Measure: Demilitarization: No Flig:	-1.000/+1.000
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -25.0/+125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.550 inches Body Diameter: 0.102 inches Body Length: 0.125 fire air Style Designator: Axial terminal each end Test Data Document: 18338-123362 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: - Demilitarization: No Fig:	Ambient Tempurature In Deg Celsius At Full Rated Power:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -25.0/+125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.550 inches Body Diameter: 0.102 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.125 fee air Style Designator: Axial terminal each end Test Data Document: 18338-123362 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	70.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -25.0/+125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.550 inches Body Diameter: 0.102 inches Body Diameter: 0.102 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 18338-123362 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Sheft Life: N/a Unit Of Measure: Demilitarization: No Fig:	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
-25.0/+125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.550 inches Body Diameter: 0.102 inches Body Diameter: 0.102 inches Body Length: 0.250 inches Power Dissipation Rating in Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 18338-123362 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Sheft Life: N/a Unit Of Measure: Demilitarization: No Fig:	175.0
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.550 inches Body Diameter: 0.102 inches Body Length: 0.250 inches Power Dissipation Rating in Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 18338-123362 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.550 inches Body Diameter: 0.102 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 18338-123362 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Via Unit Of Measure: Demilitarization: No Fig:	-25.0/+125.0
Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.550 inches Body Diameter: 0.102 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 18338-123362 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: — Demilitarization: No Fig:	Inclosure Method:
Wire lead Reliability Indicator: Not established Terminal Length: 1.550 inches Body Diameter: 0.102 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 18338-123362 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Filg:	Encapsulated
Reliability Indicator: Not established Terminal Length: 1.550 inches Body Diameter: 0.102 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 18338-123362 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Terminal Type:
Not established Terminal Length: 1.550 inches Body Diameter: 0.102 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 18338-123362 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Wire lead
Terminal Length: 1.550 inches Body Diameter: 0.102 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 18338-123362 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Reliability Indicator:
1.550 inches Body Diameter: 0.102 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 18338-123362 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Not established
Body Diameter: 0.102 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 18338-123362 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Terminal Length:
Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 18338-123362 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	1.550 inches
Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 18338-123362 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Body Diameter:
O.250 inches Power Dissipation Rating In Watts: O.125 free air Style Designator: Axial terminal each end Test Data Document: 18338-123362 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.102 inches
Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 18338-123362 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Body Length:
O.125 free air Style Designator: Axial terminal each end Test Data Document: 18338-123362 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.250 inches
Style Designator: Axial terminal each end Test Data Document: 18338-123362 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Power Dissipation Rating In Watts:
Axial terminal each end Test Data Document: 18338-123362 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.125 free air
Test Data Document: 18338-123362 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Style Designator:
18338-123362 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Axial terminal each end
excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Test Data Document:
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	18338-123362 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
N/a Unit Of Measure: Demilitarization: No Fiig:	excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	-
Fiig:	Demilitarization:
	No
A001a0	Fiig:
	A001a0