NSN 5905-00-505-5023

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-505-5023 **Section Quantity:** 3 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 0.9970 inches Pilot Length: 0.0660 inches **Undercut Diameter:** 1.168 inches **Undercut Width:** 0.0740 inches **Body Diameter:** 1.645 inches **Body Length:** 3.336 inches

Mounting Hole/stud Circle Diameter:

0.695 inches

Shaft Style:

Round, slotted

Actuator Type:

Double ended shaft

Fragility Factor:

Moderately rugged

Terminal Location:

Longitudinally positioned on the circumference

Mounting Method:

Bracket

Features Provided:

Humidity proof

Electrical Resistance Per Section:

20.0 kilohms 3rd section

Resistance Tolerance Per Section In Percent:

-5.0 to 5.0 all sections

Standard Taper Curve Per Section:

A all sections

Terminal Type And Quantity:

18 tab, solder lug

Shelf Life:

N/a

NSN 5905-00-505-5023

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A002a0