Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-505-5023

## Section Quantity:

3

Body Style:

Cylindrical servo mounted

# **Reliability Indicator:**

Not established

## **Pilot Diameter:**

0.9970 inches

#### Pilot Length:

0.0660 inches

### **Undercut Diameter:**

1.168 inches

#### Undercut Width:

0.0740 inches

#### Body Diameter:

# 1.645 inches

Body Length:

#### 3.336 inches

Mounting Hole/stud Circle Diameter:

0.695 inches

Shaft Style:

Round, slotted

#### Actuator Type:

Double ended shaft

#### **Fragility Factor:**

Moderately rugged

#### **Terminal Location:**

Longitudinally positioned on the circumference

#### **Mounting Method:**

Bracket

#### **Features Provided:**

Humidity proof

#### **Electrical Resistance Per Section:**

20.0 kilohms 3rd section

## **Resistance Tolerance Per Section In Percent:**

-5.0 to 5.0 all sections

## Standard Taper Curve Per Section:

A all sections

## **Terminal Type And Quantity:**

18 tab, solder lug

#### Shelf Life:

N/a

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0