

View Online at <https://aerobasegroup.com/nsn/5905-00-506-4175>

**Section Quantity:**

1

**Body Style:**

Rectangular w/mounting holes

**Reliability Indicator:**

Not established

**Overall Length:**

0.715 inches

**Terminal Length:**

0.300 inches

**Overall Height:**

0.375 inches

**Overall Width:**

0.203 inches

**Mounting Slot Width:**

0.060 inches

**Shaft Diameter:**

0.090 inches

**Shaft Length:**

0.040 inches

**Body Length:**

0.375 inches

**Body Width:**

0.203 inches

**Body Height:**

0.375 inches

**Shaft Style:**

Round, slotted

**Actuator Type:**

Single shaft

**Maximum Starting Torque:**

5.00 inch-ounces

**Center To Center Distance Between Terminals:**

0.200 inches

**Lateral Distance Between Mounting Hole Centers:**

0.419 inches

**Mounting Facility Quantity:**

2

**Terminal Location:**

Rear end

**Mounting Method:**

Slot and terminal

**Features Provided:**

Nonmetallic shaft

**Electrical Resistance Per Section:**

10.0 ohms single section

**Rotary Actuator Travel In Angular Deg:**

9000.0

**Center To Center Distance Between Center Terminal And Outside Terminal:**

0.100 inches

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

175.0 single section

**Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:**

-100.0 to 100.0 single section

**Power Dissipation Rating Per Section In Watts:**

0.5 free air single section

**Resistance Tolerance Per Section In Percent:**

-10.0 to 10.0 single section

**Actuator Travel Control Feature:**

Clutch

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

85.0 single section

**Standard Taper Curve Per Section:**

A single section

**Terminal Type And Quantity:**

3 pin

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0