NSN 5905-00-506-6135

Specification Data:

81349-mil-r-39009/1 government specification

Inductive Wire Wound Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-506-6135

Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:

-50.0/+50.0	
Electrical Resistance:	
3.920 ohms	
Resistance Tolerance In Percent:	
-1.000/+1.000	
Ambient Tempurature In Deg Celsius At Full Rated Power:	
25.0	
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:	
275.0	
Tempurature Range Of Tempurature Coefficient In Deg Celsius:	
-55.0/+275.0	
Inclosure Method:	
Encased	
Terminal Type:	
Tab, solder lug	
Reliability Indicator:	
Established	
Reliability Failure Rate Level In Percent:	
0.010	
Terminal Length:	
0.438 inches	
Body Length:	
1.062 inches	
Body Width:	
0.531 inches	
Body Height:	
0.562 inches	
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:	
0.719 inches	
Power Dissipation Rating In Watts:	
8.000 free air	
Terminal Width:	
0.140 inches	
Mounting Hole Size:	
0.125 inches	
Style Designator:	
Axial terminal (s)	
Test Data Document:	
81349-mil-r-39009 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification	
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	

NSN 5905-00-506-6135

Inductive Wire Wound Fixed Resistor - Page 2 of 2



Sneit	Lite:
N/a	

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A001a0