NSN 5905-00-506-6608

-50.0/+50.0

4.020 ohms

Electrical Resistance:

Noninductive Wire Wound Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-506-6608

Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:

Resistance Tolerance In Percent:			
-1.000/+1.000			
Ambient Tempurature In Deg Celsius At Full Rated Power:			
25.0			
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:			
275.0			
Tempurature Range Of Tempurature Coefficient In Deg Celsius:			
-55.0/+275.0			
Inclosure Method:			
Encased			
Terminal Type:			
Tab, solder lug			
Reliability Indicator:			
Established			
Reliability Failure Rate Level In Percent:			
0.010			
Terminal Length:			
0.312 inches			
Body Length:			
0.750 inches			
Body Width:			
0.438 inches			
Body Height:			
0.406 inches			
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:			
0.562 inches			
Power Dissipation Rating In Watts:			
6.000 free air			
Mounting Hole Size:			
0.094 inches			
Style Designator:			
Axial terminal (s)			
Test Data Document:			
81349-mil-r-39009 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification			
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain			
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).			
Specification Data:			
81349-mil-r-39009/2 government specification			
Shelf Life:			
N/a			

NSN 5905-00-506-6608

Noninductive Wire Wound Fixed Resistor - Page 2 of 2



nıt	<i>(</i>)+	Measure:

--

Demilitarization:

No

Fiig:

A001a0