NSN 5905-00-509-8821

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-509-8821

Section Quantity:
1
Body Style:
Cylindrical servo mounted
Reliability Indicator:
Not established
Pilot Diameter:
0.7500 inches
Pilot Length:
0.0620 inches
Overall Length:
0.697 inches
Undercut Diameter:
0.875 inches
Undercut Width:
0.0620 inches
Body Diameter:
0.875 inches
Shaft Diameter:
0.125 inches
Shaft Length:
Between 0.756 inches and 0.813 inches
Body Length:
0.635 inches
Overall Diameter:
0.937 inches
Mounting Lip Diameter:
0.8750 inches
Mounting Lip Depth:
0.0620 inches
Shaft Style:
Round
Shaft Bearing Type:
Ball
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
320.0
Maximum Starting Torque:
0.10 inch-ounces
Maximum Running Torque:

0.10 inch-ounces

NSN 5905-00-509-8821

Precision Wire Wound Variable Resistor - Page 2 of 3



Shaft Runout:
0.001 inches
Pilot Diameter Runout:
0.00100 inches
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Clamp ring
Electrical Resistance Per Section:
20.000 kilohms single section
Tap Location From Ccw Terminal Per Section In Deg Of Effective Electrical Rotation:
180.0 single section
Rotary Actuator Travel In Angular Deg:
360.0
Function Conformity Tolerance Per Section:
-1.00/+1.00 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
145.0 single section
Power Dissipation Rating Per Section In Watts:
0.5 free air single section
Function Conformity Per Section:
Single section independent linearity
Fixed Tap Quantity Per Section:
1 single section
Tap Location Tolerance Per Section:
-3.0/+3.0 degrees angular rotation single section
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Actuator Travel Control Feature:
Continuous motion
Function Characteristic Per Section:
Single section linear
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
-20.0/+20.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
125.0 single section
Terminal Type And Quantity:
4 solder stud
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

NSN 5905-00-509-8821

Precision Wire Wound Variable Resistor - Page 3 of 3



Fiig:

A002a0