

View Online at <https://aerobasegroup.com/nsn/5905-00-513-5750>

**Section Quantity:**

1

**Body Style:**

Cylindrical servo mounted

**Reliability Indicator:**

Not established

**Pilot Diameter:**

2.6250 inches

**Pilot Length:**

0.0620 inches

**Overall Length:**

2.188 inches

**Undercut Diameter:**

2.875 inches

**Undercut Width:**

0.0620 inches

**Body Diameter:**

3.0000 inches

**Mounting Hole Diameter:**

0.093 inches

**Angle Of Mounting Hole In Deg:**

90.0

**Angle Between Centerlines Of Mounting Holes In Deg:**

120.0

**Shaft Diameter:**

0.375 inches

**Shaft Length:**

1.000 inches

**Body Length:**

1.188 inches

**Overall Diameter:**

3.187 inches

**Mounting Lip Diameter:**

3.0000 inches

**Mounting Lip Depth:**

0.0620 inches

**Mounting Hole/stud Circle Diameter:**

2.750 inches

**Shaft Style:**

Round

**Shaft Bearing Type:**

Ball

**Actuator Type:**

Single shaft

**Effective Electrical Rotation In Deg Angular Rotation:**

315.0

**Maximum Starting Torque:**

2.00 inch-ounces

**Maximum Running Torque:**

0.75 inch-ounces

**Shaft End Play:**

0.00200 inches

**Shaft Runout:**

0.001 inches

**Lateral Runout:**

0.002 inches

**Pilot Diameter Runout:**

0.00150 inches

**Shaft Radial Play:**

0.003 inches

**Mechanical Backlash In Deg Angular Rotation:**

10.0

**Mounting Facility Quantity:**

3

**Terminal Location:**

Radially positioned over less than half the circumference

**Mounting Method:**

Unthreaded hole

**Electrical Resistance Per Section:**

72.000 kilohms single section

**Rotary Actuator Travel In Angular Deg:**

315.0

**Function Conformity Tolerance Per Section:**

-0.50/+0.50 single section

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

325.0 single section

**Power Dissipation Rating Per Section In Watts:**

2.0 free air single section

**Function Conformity Per Section:**

Single section independent linearity

**Fixed Tap Quantity Per Section:**

1 single section

**Tap Location Tolerance Per Section:**

-1.0/+1.0 ohms single section

**Resistance Tolerance Per Section In Percent:**

-5.0/+5.0 single section

**Actuator Travel Control Feature:**

Clutch

**Tap Location From Ccw Terminal Per Section In Ohms:**

36000.0 single section

**Function Characteristic Per Section:**

Single section linear

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

25.0 single section

**Terminal Type And Quantity:**

4 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A002a0