NSN 5905-00-514-1973

Film Fixed Resistor Network - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-514-1973

Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
-100.0/+100.0
Electrical Resistance:
62.000 ohms
Resistance Tolerance In Percent:
-5.000/+5.000
Ambient Tempurature In Deg Celsius At Full Rated Power:
70.0
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
150.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius:
-55.0/+150.0
Inclosure Method:
Encapsulated
Terminal Quantity:
14
Terminal Type:
Tab, solder lug
Reliability Indicator:
Not established
Terminal Length:
0.100 inches
0.100 inches Body Length:
Body Length:
Body Length: Between 0.660 inches and 0.785 inches
Body Length: Between 0.660 inches and 0.785 inches Body Width:
Body Length: Between 0.660 inches and 0.785 inches Body Width: Between 0.220 inches and 0.290 inches
Body Length: Between 0.660 inches and 0.785 inches Body Width: Between 0.220 inches and 0.290 inches Body Height:
Body Length: Between 0.660 inches and 0.785 inches Body Width: Between 0.220 inches and 0.290 inches Body Height: 0.200 inches
Body Length: Between 0.660 inches and 0.785 inches Body Width: Between 0.220 inches and 0.290 inches Body Height: 0.200 inches Schematic Diagram Designator:
Body Length: Between 0.660 inches and 0.785 inches Body Width: Between 0.220 inches and 0.290 inches Body Height: 0.200 inches Schematic Diagram Designator: Isolated array
Body Length: Between 0.660 inches and 0.785 inches Body Width: Between 0.220 inches and 0.290 inches Body Height: 0.200 inches Schematic Diagram Designator: Isolated array Power Dissipation Rating In Watts:
Body Length: Between 0.660 inches and 0.785 inches Body Width: Between 0.220 inches and 0.290 inches Body Height: 0.200 inches Schematic Diagram Designator: Isolated array Power Dissipation Rating In Watts: 0.120 total network
Body Length: Between 0.660 inches and 0.785 inches Body Width: Between 0.220 inches and 0.290 inches Body Height: 0.200 inches Schematic Diagram Designator: Isolated array Power Dissipation Rating In Watts: 0.120 total network Terminal Width:
Body Length: Between 0.660 inches and 0.785 inches Body Width: Between 0.220 inches and 0.290 inches Body Height: 0.200 inches Schematic Diagram Designator: Isolated array Power Dissipation Rating In Watts: 0.120 total network Terminal Width: 0.023 inches
Body Length: Between 0.660 inches and 0.785 inches Body Width: Between 0.220 inches and 0.290 inches Body Height: 0.200 inches Schematic Diagram Designator: Isolated array Power Dissipation Rating In Watts: 0.120 total network Terminal Width: 0.023 inches Cubic Measure:
Body Length: Between 0.660 inches and 0.785 inches Body Width: Between 0.220 inches and 0.290 inches Body Height: 0.200 inches Schematic Diagram Designator: Isolated array Power Dissipation Rating In Watts: 0.120 total network Terminal Width: 0.023 inches Cubic Measure: 0.0456 cubic inches
Body Length: Between 0.660 inches and 0.785 inches Body Width: Between 0.220 inches and 0.290 inches Body Height: 0.200 inches Schematic Diagram Designator: Isolated array Power Dissipation Rating In Watts: 0.120 total network Terminal Width: 0.023 inches Cubic Measure: 0.0456 cubic inches Identical Value Resistor Quantity:
Body Length: Between 0.660 inches and 0.785 inches Body Width: Between 0.220 inches and 0.290 inches Body Height: 0.200 inches Schematic Diagram Designator: Isolated array Power Dissipation Rating In Watts: 0.120 total network Terminal Width: 0.023 inches Cubic Measure: 0.0456 cubic inches Identical Value Resistor Quantity: 7 each resistor

N/a

NSN 5905-00-514-1973

Film Fixed Resistor Network - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A001a0