

View Online at <https://aerobasegroup.com/nsn/5905-00-514-1983>

**Temperature Coefficient Of Resistance In Ppm Per Deg Celsius:**

-50.0 to 50.0

**Electrical Resistance:**

10.000 kilohms lowest resistance value

**Resistance Tolerance In Percent:**

-5.000 to 5.000 each resistor

**Ambient Temperature In Deg Celsius At Full Rated Power:**

70.0

**Ambient Temperature In Deg Celsius At Zero Percent Rated Power:**

105.0

**Temperature Range Of Temperature Coefficient In Deg Celsius:**

-55.0 to 105.0

**Inclosure Method:**

Encapsulated

**Terminal Quantity:**

16

**Terminal Type:**

Tab, solder lug

**Reliability Indicator:**

Not established

**Terminal Length:**

Between 0.080 inches and 0.150 inches

**Body Length:**

Between 0.784 inches and 0.876 inches

**Body Width:**

Between 0.240 inches and 0.305 inches

**Body Height:**

0.200 inches

**Schematic Diagram Designator:**

Balanced ladder network

**Power Dissipation Rating In Watts:**

0.250 each resistor

**Terminal Width:**

Between 0.015 inches and 0.022 inches

**Cubic Measure:**

0.045 cubic inches

**Identical Value Resistor Quantity:**

6 highest resistance value

**Precious Material And Location:**

Terminal surfaces gold

**Style Designator:**

Dual inline

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A001a0