## NSN 5905-00-514-1983

Film Fixed Resistor Network - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-514-1983

Tempurature	Coefficient	Of Resistance	In Ppm	Per Deg	Celsius:
-------------	-------------	---------------	--------	---------	----------

-50.0 to 50.0

**Electrical Resistance:** 

10.000 kilohms lowest resistance value

**Resistance Tolerance In Percent:** 

-5.000 to 5.000 each resistor

Ambient Tempurature In Deg Celsius At Full Rated Power:

70.0

Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:

105.0

**Tempurature Range Of Tempurature Coefficient In Deg Celsius:** 

-55.0 to 105.0

**Inclosure Method:** 

Encapsulated

**Terminal Quantity:** 

16

**Terminal Type:** 

Tab, solder lug

**Reliability Indicator:** 

Not established

**Terminal Length:** 

Between 0.080 inches and 0.150 inches

**Body Length:** 

Between 0.784 inches and 0.876 inches

**Body Width:** 

Between 0.240 inches and 0.305 inches

**Body Height:** 

0.200 inches

**Schematic Diagram Designator:** 

Balanced ladder network

**Power Dissipation Rating In Watts:** 

0.250 each resistor

**Terminal Width:** 

Between 0.015 inches and 0.022 inches

**Cubic Measure:** 

0.045 cubic inches

**Identical Value Resistor Quantity:** 

6 highest resistance value

**Precious Material And Location:** 

Terminal surfaces gold

**Style Designator:** 

**Dual inline** 

## NSN 5905-00-514-1983

Film Fixed Resistor Network - Page 2 of 2



Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A001a0