NSN 5905-00-515-2339

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-515-2339 **Section Quantity:** 1 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 0.6250 inches Pilot Length: 0.0620 inches **Undercut Diameter:** 0.875 inches **Undercut Width:** 0.1250 inches **Body Diameter:** 0.875 inches **Angle Of Mounting Hole In Deg:** 120.0 **Angle Between Centerlines Of Mounting Holes In Deg:** 120.0 **Shaft Diameter:** 0.125 inches **Shaft Length:** 0.375 inches **Body Length:** 1.571 inches **Mounting Lip Diameter:** 0.8750 inches **Mounting Lip Depth:** 0.0620 inches **Mounting Hole/stud Circle Diameter:** 0.438 inches **Shaft Style:** Round **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 3600.0 **Maximum Starting Torque:**

0.60 inch-ounces **Maximum Running Torque:**

0.50 inch-ounces

NSN 5905-00-515-2339

Precision Wire Wound Variable Resistor - Page 2 of 3



Shaft End Play:
0.00500 inches
Shaft Runout:
0.001 inches
Lateral Runout:
0.003 inches
Pilot Diameter Runout:
0.00150 inches
Shaft Radial Play:
0.002 inches
Terminal Location:
Longitudinally positioned on the circumference
Mounting Method:
Clamp ring
Features Provided:
Nonmetallic shaft
Electrical Resistance Per Section:
5.000 kilohms single section
Rotary Actuator Travel In Angular Deg:
3600.0
Function Conformity Tolerance Per Section:
-0.05/+0.05 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
85.0 single section
Power Dissipation Rating Per Section In Watts:
1.5 free air single section
Function Conformity Per Section:
Single section independent linearity
Fixed Tap Quantity Per Section:
1 single section
Tap Location Tolerance Per Section:
-2.0/+2.0 degrees angular rotation single section
Resistance Tolerance Per Section In Percent:
-3.0/+3.0 single section
Actuator Travel Control Feature:
Stops
Tap Location From Ccw Terminal Per Section In Ohms:
2500.0 single section
Function Characteristic Per Section:
Single section linear
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:

40.0 single section

+0.0/+130.0 single section

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

NSN 5905-00-515-2339

Precision Wire Wound Variable Resistor - Page 3 of 3



Terminal Type And Quantity:
4 turret
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A002a0