

View Online at <https://aerobasegroup.com/nsn/5905-00-515-2439>

Section Quantity:

1

Body Style:

Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

Between 0.9683 inches and 0.9688 inches

Pilot Length:

0.0620 inches

Overall Length:

0.975 inches

Undercut Diameter:

0.968 inches

Undercut Width:

0.0570 inches

Body Diameter:

1.062 inches

Shaft Diameter:

0.1248 inches

Shaft Length:

0.500 inches

Body Length:

0.475 inches

Overall Diameter:

1.233 inches

Mounting Lip Diameter:

1.0620 inches

Mounting Lip Depth:

0.0620 inches

Shaft Style:

Round

Shaft Bearing Type:

Ball

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

340.0

Shaft End Play:

0.005 inches

Shaft Runout:

0.002 inches

Lateral Runout:

0.002 inches

Pilot Diameter Runout:

0.001 inches

Shaft Radial Play:

0.002 inches

Mechanical Backlash In Deg Angular Rotation:

0.1

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Clamp ring

Electrical Resistance Per Section:

5.0 kilohms single section

Rotary Actuator Travel In Angular Deg:

340.0

Function Conformity Tolerance Per Section:

-0.50/+0.50 single section

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-30.0/+30.0 single section

Power Dissipation Rating Per Section In Watts:

1.25 free air single section

Function Conformity Per Section:

Single section independent linearity

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

Actuator Travel Control Feature:

Continuous motion

Function Characteristic Per Section:

Single section linear

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Terminal Type And Quantity:

3 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0