

View Online at <https://aerobasegroup.com/nsn/5905-00-516-0814>

Section Quantity:

1

Body Style:

Cylindrical servo mounted

Pilot Diameter:

0.75000 inches

Pilot Length:

0.06250 inches

Overall Length:

1.187 inches

Undercut Diameter:

0.750 inches

Undercut Width:

0.06250 inches

Body Diameter:

0.875 inches

Shaft Diameter:

0.1248 inches

Body Length:

0.687 inches

Mounting Lip Diameter:

0.87500 inches

Mounting Lip Depth:

0.06250 inches

Mounting Hole/stud Circle Diameter:

0.547 inches

Shaft Style:

Round

Shaft Bearing Type:

Bearing

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

350.0

Maximum Starting Torque:

0.10 inch-ounces

Maximum Running Torque:

0.10 inch-ounces

Shaft End Play:

0.00005 inches

Shaft Runout:

0.002 inches

Lateral Runout:

0.002 inches

Pilot Diameter Runout:

0.00002 inches

Shaft Radial Play:

0.002 inches

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Unthreaded hole

Electrical Resistance Per Section:

2.000 kilohms single section

Rotary Actuator Travel In Angular Deg:

360.0

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

Power Dissipation Rating Per Section In Watts:

1.2 free air single section

Fixed Tap Quantity Per Section:

1 single section

Resistance Tolerance Per Section In Percent:

-20.0 to 20.0 single section

Actuator Travel Control Feature:

Continuous motion

Temperature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:

-20.0 to 20.0 single section

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 binding post

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0