

View Online at <https://aerobasegroup.com/nsn/5905-00-517-9330>

**Section Quantity:**

1

**Body Style:**

Rectangular w/mounting holes/slots

**Reliability Indicator:**

Not established

**Terminal Length:**

Between 0.469 inches and 0.531 inches

**Mounting Hole Diameter:**

0.093 inches

**Shaft Diameter:**

Between 0.100 inches and 0.130 inches

**Shaft Length:**

Between 0.036 inches and 0.080 inches

**Body Length:**

Between 1.218 inches and 1.282 inches

**Body Width:**

Between 0.300 inches and 0.330 inches

**Body Height:**

Between 0.180 inches and 0.200 inches

**Shaft Style:**

Round, slotted

**Actuator Type:**

Single shaft

**Effective Electrical Rotation In Deg Angular Rotation:**

Between 6120.0 and 9720.0

**Maximum Starting Torque:**

8.00 inch-ounces

**Maximum Running Torque:**

8.00 inch-ounces

**Center To Center Distance Between Terminals:**

Between 0.690 inches and 0.710 inches

**Fragility Factor:**

Moderately rugged

**Lateral Distance Between Mounting Hole Centers:**

1.000 inches

**Mounting Facility Quantity:**

2

**Terminal Location:**

Lower adjacent side two rows

**Mounting Method:**

Unthreaded hole

**Features Provided:**

Humidity proof

**Cubic Measure:**

0.075 cubic inches

**Electrical Resistance Per Section:**

500.0 ohms single section

**Rotary Actuator Travel In Angular Deg:**

Between 6120.0 and 9720.0

**Center To Center Distance Between Center Terminal And Outside Terminal:**

Between 0.300 inches and 0.400 inches

**Resistance Temperature Characteristic Range Per Section In Percent:**

+0.0 to 4.5 -55 degrees celsius single section and +0.0 to 2.5 -25 degrees celsius single section and -1.5 to 1.5 85 degrees celsius single section and -4.0 to 4.0 125 degrees celsius single section

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

150.0 single section

**Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:**

-250.0 to 250.0 single section

**Power Dissipation Rating Per Section In Watts:**

0.75 free air single section

**Resistance Tolerance Per Section In Percent:**

-10.0 to 10.0 single section

**Actuator Travel Control Feature:**

Clutch

**Criticality Code Justification:**

Feat

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

85.0 single section

**Standard Taper Curve Per Section:**

A single section

**Special Features:**

Aircraft, f-111

**Test Data Document:**

81349-mil-r-22097 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

3 pin

**Specification Data:**

81349-mil-r-22097/2 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No