NSN 5905-00-517-9330

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-517-9330

View Online at https://aerobasegroup.com/nsn/5905-00-51	7
Section Quantity:	
1	
Body Style:	
Rectangular w/mounting holes/slots	
Reliability Indicator:	
Not established	
Terminal Length:	
Between 0.469 inches and 0.531 inches	
Mounting Hole Diameter:	
0.093 inches	
Shaft Diameter:	
Between 0.100 inches and 0.130 inches	
Shaft Length:	
Between 0.036 inches and 0.080 inches	
Body Length:	
Between 1.218 inches and 1.282 inches	
Body Width:	
Between 0.300 inches and 0.330 inches	
Body Height:	
Between 0.180 inches and 0.200 inches	
Shaft Style:	
Round, slotted	
Actuator Type:	
Single shaft	
Effective Electrical Rotation In Deg Angular Rotation:	
Between 6120.0 and 9720.0	
Maximum Starting Torque:	
8.00 inch-ounces	
Maximum Running Torque:	
8.00 inch-ounces	
Center To Center Distance Between Terminals:	
Between 0.690 inches and 0.710 inches	
Fragility Factor:	
Moderately rugged	
Lateral Distance Between Mounting Hole Centers:	
1.000 inches	
Mounting Facility Quantity:	
2	
Terminal Location:	
Lower adjacent side two rows	
Mounting Method:	

Unthreaded hole

NSN 5905-00-517-9330

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Features Provided:
Humidity proof
Cubic Measure:
0.075 cubic inches
Electrical Resistance Per Section:
500.0 ohms single section
Rotary Actuator Travel In Angular Deg:
Between 6120.0 and 9720.0
Center To Center Distance Between Center Terminal And Outside Terminal:
Between 0.300 inches and 0.400 inches
Resistance Tempurature Characteristic Range Per Section In Percent:
+0.0 to 4.5 -55 degrees celsius single section and +0.0 to 2.5 -25 degrees celsius single section and -1.5 to 1.5 85 degrees celsius sing
section and -4.0 to 4.0 125 degrees celsius single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-250.0 to 250.0 single section
Power Dissipation Rating Per Section In Watts:
0.75 free air single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Actuator Travel Control Feature:
Clutch
Criticality Code Justification:
Feat
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
85.0 single section
Standard Taper Curve Per Section:
A single section
Special Features:
Aircraft, f-111
Test Data Document:
81349-mil-r-22097 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
3 pin
Specification Data:
81349-mil-r-22097/2 government specification
Shelf Life:
N/a

No

Unit Of Measure:

Demilitarization: