Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-518-5593

Section Quantity: 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** Between 0.937 inches and 1.187 inches **Body Diameter:** Between 1.032 inches and 1.156 inches Shaft Diameter: Between 0.248 inches and 0.251 inches Shaft Length: Between 0.469 inches and 0.531 inches Mounting Bushing Length: Between 0.485 inches and 0.515 inches **Body Length:** Between 0.468 inches and 0.656 inches Shaft Style: Round, slotted Actuator Type: Single shaft Effective Electrical Rotation In Deg Angular Rotation: Between 309.0 and 320.0 **Nonturn Device Location:** At 9 oclock **Nonturn Device Radius:** Between 0.515 inches and 0.547 inches **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Locking bushing **Electrical Resistance Per Section:** 500.0 kilohms single section **Rotary Actuator Travel In Angular Deg:** Between 309.0 and 320.0



Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

120.0 single section

Power Dissipation Rating Per Section In Watts:

2.0 free air single section

Resistance Tolerance Per Section In Percent:

-10.0 to 10.0 single section

Actuator Travel Control Feature:

Stops

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Test Data Document:

81349-mil-r-94 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

3 tab, solder lug

Specification Data:

81349-mil-r-94/5 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0