NSN 5905-00-518-7558

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-518-7558 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 1.031 inches **Terminal Length:** 0.243 inches First Flat Length: Between 0.161 inches and 0.191 inches Flat Height: 0.125 inches **Body Diameter:** 1.438 inches **Shaft Diameter:** Between 0.248 inches and 0.250 inches **Shaft Length:** 0.609 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 0.375 inches **Shaft Style:** Round, parallel flatted **Actuator Type:** Single shaft **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Standard bushing

Features Provided:
Nonmetallic shaft

Electrical Resistance Per Section:

4.000 ohms single section

NSN 5905-00-518-7558

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Power Dissipation Rating Per Section In Watts: 3.0 free air single section Resistance Tolerance Per Section In Percent: +0.0 to 20.0 single section Standard Taper Curve Per Section: A single section Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a Unit Of Measure: -- Demilitarization: No

Fiig: A002a0