## NSN 5905-00-518-8255

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-518-8255 **Section Quantity:** 2 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 1.062 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 2.000 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 1.188 inches **Shaft Style:** Round **Actuator Type:** Single shaft **Nonturn Device Location:** At 9 oclock **Nonturn Device Radius:** 0.531 inches **Screw Thread Diameter:** 0.375 inches

**Screw Thread Series Designator:** 

Screw Thready Qty Per Inch (tpi):

32.0

**Terminal Location:** 

Radially positioned over less than half the circumference

**Mounting Method:** 

Standard bushing

**Electrical Resistance Per Section:** 

50.0 kilohms all sections

**Power Dissipation Rating Per Section In Watts:** 

2.0 free air all sections

**Resistance Tolerance Per Section In Percent:** 

-10.0 to 10.0 all sections

**Standard Taper Curve Per Section:** 

A all sections

## NSN 5905-00-518-8255

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A002a0