Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



Nonprecision Nonwire wound variable Resistor - Page 1 of 2
View Online at https://aerobasegroup.com/nsn/5905-00-518-9286
Section Quantity:
2
Body Style:
Cylindrical bushing mounted
Body Diameter:
1.140 inches
Shaft Diameter:
Between 0.248 inches and 0.250 inches
Shaft Length:
0.880 inches
Mounting Bushing Length:
0.375 inches
Body Length:
Shaft Style: Round
Actuator Type:
Single shaft
Nonturn Device Location:
At 9 oclock
Nonturn Device Radius:
0.531 inches
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
2.000 kilohms all sections
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 all sections
Power Dissipation Rating Per Section In Watts:
2.0 free air all sections
Resistance Tolerance Per Section In Percent:
-20.0 to 20.0 all sections
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 all sections



Standard Taper Curve Per Section:

A all sections

Special Features:

0.375 in. Bushing Ig

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0