NSN 5905-00-518-9927

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-518-9927

-500.0/+500.0 Electrical Resistance: 18.000 kilohms Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 40.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 120.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 120.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+105.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.937 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document: 8149-milit 105909 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Shelf Life: N/a Unit of Measure:	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
Resistance Tolerance in Percent: -1.000/41-000 Ambient Tempurature in Deg Celsius At Full Rated Power: 40,0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 120.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.0/+105.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.296 inches Body Length: 0.937 inches Power Dissipation Rating in Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr10509b specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, inclustry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.) Sheff Life: N/a Unit Of Measure: Demilitarization: No Filig:	-500.0/+500.0
Resistance Tolerance in Percent: -1.000/+1.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 40.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 120.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.0/+105.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.296 inches Body Length: 0.937 inches Power Dissipation Rating in Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-milit 10590b specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format: excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as 'typical', "average', ", etc.). Shelf Life: Na Unit Of Measure:	Electrical Resistance:
Ambient Tempurature In Deg Celsius At Full Rated Power: 40.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 120.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+105.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.296 inches Body Length: 0.397 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-milir 10509b specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Filg:	18.000 kilohms
Ambient Tempurature In Deg Celsius At Full Rated Power: 40.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 120.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.0/+105.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.296 inches Body Length: 0.937 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-milit 10509b specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Filg:	Resistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 120.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+105.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.296 inches Body Length: 0.937 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-milir10509b specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	-1.000/+1.000
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 120.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+105.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.296 inches Body Length: 0.937 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Tests Data Document: 81349-mill 10509b specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	Ambient Tempurature In Deg Celsius At Full Rated Power:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+105.0 Inclosure Method: Encapsulated Terminal Type: Wrire lead Reliability Indicator: Not established Body Diameter: 0.296 inches Body Length: 0.937 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-millr10509b specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	40.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+105.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.296 inches Body Length: 0.937 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mili10509b specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.296 inches Body Length: 0.937 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr10509b specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	120.0
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.296 inches Body Length: 0.937 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mill*10509b specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.296 inches Body Length: 0.937 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr10509b specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	-55.0/+105.0
Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.296 inches Body Length: 0.937 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr10509b specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Inclosure Method:
Wire lead Reliability Indicator: Not established Body Diameter: 0.296 inches Body Length: 0.937 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr10509b specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Encapsulated
Reliability Indicator: Not established Body Diameter: 0.296 inches Body Length: 0.937 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr10509b specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Terminal Type:
Note established Body Diameter: 0.296 inches Body Length: 0.937 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr10509b specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Wire lead
Body Diameter: 0.296 inches Body Length: 0.937 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr10509b specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Reliability Indicator:
0.296 inches Body Length: 0.937 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr10509b specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Not established
Body Length: 0.937 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr10509b specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig:	Body Diameter:
0.937 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr10509b specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.296 inches
Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr10509b specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Body Length:
1.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr10509b specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.937 inches
Style Designator: Axial terminal each end Test Data Document: 81349-milr10509b specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Power Dissipation Rating In Watts:
Axial terminal each end Test Data Document: 81349-milr10509b specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	1.000 free air
Test Data Document: 81349-milr10509b specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Style Designator:
81349-milr10509b specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Axial terminal each end
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Test Data Document:
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	81349-milr10509b specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
N/a Unit Of Measure: Demilitarization: No Fiig:	environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
	No
A001a0	Fiig:
	A001a0