

View Online at https://aerobasegroup.com/nsn/5905-00-521-0298

Section Quantity:

1

Body Style:

Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

0.9688 inches

Pilot Length:

0.0620 inches

Overall Length:

2.150 inches

Undercut Diameter:

0.96880 inches

Undercut Width:

0.0620 inches

Body Diameter:

1.062 inches

Shaft Diameter:

0.1248 inches

Shaft Length:

Between 0.218 inches and 0.402 inches

Body Length:

1.530 inches

Overall Diameter:

1.208 inches

Mounting Lip Diameter:

1.0620 inches

Mounting Lip Depth:

0.0620 inches

Shaft Style:

Round

Shaft Bearing Type:

Bearing

Actuator Type:

Double ended shaft

Effective Electrical Rotation In Deg Angular Rotation:

352.0

Maximum Starting Torque:

0.50 inch-ounces

Maximum Running Torque:

0.30 inch-ounces



Shaft End Play:

0.00500 inches

Shaft Runout:

0.001 inches

Lateral Runout:

0.001 inches

Pilot Diameter Runout:

0.00100 inches

Shaft Radial Play:

0.002 inches

Mechanical Backlash In Deg Angular Rotation:

0.1

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Clamp ring

Electrical Resistance Per Section:

2.500 kilohms single section

Rotary Actuator Travel In Angular Deg:

360.0

Function Conformity Tolerance Per Section:

-0.15/+0.15 single section

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-30.0/+30.0 single section

Power Dissipation Rating Per Section In Watts:

1.5 free air single section

Function Conformity Per Section:

Single section absolute linearity

Resistance Tolerance Per Section In Percent:

-5.0/+5.0 single section

Actuator Travel Control Feature:

Continuous motion

Function Characteristic Per Section:

Single section linear

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

25.0 single section

Special Features:

Two additional dummy cups included

Test Data Document:

50985-8872600001 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,

etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

3 turret



Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0