

View Online at <https://aerobasegroup.com/nsn/5905-00-532-0585>

Section Quantity:

1

Body Style:

Rectangular

Reliability Indicator:

Not established

Terminal Length:

Between 0.490 inches and 0.510 inches

Shaft Diameter:

Between 0.058 inches and 0.098 inches

Shaft Length:

0.045 inches

Body Length:

Between 0.490 inches and 0.510 inches

Body Width:

Between 0.180 inches and 0.230 inches

Body Height:

0.540 inches

Shaft Style:

Round, slotted

Shaft Bearing Type:

Sleeve

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

Between 7200.0 and 16200.0

Maximum Starting Torque:

5.00 inch-ounces

Maximum Running Torque:

5.00 inch-ounces

Center To Center Distance Between Terminals:

Between 0.195 inches and 0.205 inches

Fragility Factor:

Moderately rugged

Terminal Location:

Lower adjacent side single row

Mounting Method:

Terminal

Features Provided:

Humidity proof

Cubic Measure:

0.055 cubic inches

Electrical Resistance Per Section:

50.0 kilohms single section

Rotary Actuator Travel In Angular Deg:

9000.0

Center To Center Distance Between Center Terminal And Outside Terminal:

Between 0.095 inches and 0.105 inches

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-250.0 to 250.0 single section

Power Dissipation Rating Per Section In Watts:

0.5 free air single section

Resistance Tolerance Per Section In Percent:

-10.0 to 10.0 single section

Actuator Travel Control Feature:

Clutch

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

85.0 single section

Standard Taper Curve Per Section:

A single section

Test Data Document:

81349-mil-r-22097 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

3 pin

Specification Data:

81349-mil-r-22097/3 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0