NSN 5905-00-532-0610

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-532-0610

Electrical Resistance: 33.000 kilohms Resistance Tolerance In Percent: 40.500/+0.500 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 455.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.188 inches Body Length: 0.255 inches Power Dissipation Rating In Watts: 20.250 free air Style Designator: Avail terminal each end Test Data Document:
Resistance Tolerance In Percent: -0.500/+0.500 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0 Inclosure Method: -Encapsulated Terminal Type: Wire lead Reliability Indicator: -Established Reliability Failure Rate Level In Percent: -0.001
Resistance Tolerance In Percent: -0.500/+0.500 Ambient Tempurature In Deg Celsius At Full Rated Power: -125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: -175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0 Inclosure Method: Encapsulated Terminal Type:
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.188 inches Body Length: 0.625 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 125.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 10.001 Body Diameter: 10.188 inches Body Length: 10.625 inches Power Dissipation Rating In Watts: 10.250 free air Style Designator: Axial terminal each end
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.188 inches Body Length: 0.625 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.188 inches Body Length: 0.625 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end
Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.188 inches Body Length: 0.625 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end
Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 10.001 Body Diameter: 10.188 inches Body Length: 10.625 inches Power Dissipation Rating In Watts: 10.250 free air Style Designator: Axial terminal each end
Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.188 inches Body Length: 0.625 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.188 inches Body Length: 0.625 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end
Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.188 inches Body Length: 0.625 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end
Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.188 inches Body Length: 0.625 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end
Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.188 inches Body Length: 0.625 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end
Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.188 inches Body Length: 0.625 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end
Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.188 inches Body Length: 0.625 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end
Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.188 inches Body Length: 0.625 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end
Body Diameter: 0.188 inches Body Length: 0.625 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end
Body Diameter: 0.188 inches Body Length: 0.625 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end
0.188 inches Body Length: 0.625 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end
Body Length: 0.625 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end
20.625 inches Power Dissipation Rating In Watts: 20.250 free air Style Designator: Axial terminal each end
Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end
0.250 free air Style Designator: Axial terminal each end
Style Designator: Axial terminal each end
Axial terminal each end
Test Data Document:
81349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A001a0