NSN 5905-00-533-6271

Precision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-533-6271

View Online at https://aerobasegroup.com/nsn/5905-00-533-
Section Quantity:
1 Pady Style:
Body Style:
Cylindrical servo mounted
Reliability Indicator: Not established
Pilot Diameter:
Between 0.6245 inches and 0.6250 inches
Pilot Length:
Between 0.0570 inches and 0.0670 inches
Undercut Diameter:
Between 0.965 inches and 0.975 inches
Undercut Width:
Between 0.0570 inches and 0.0670 inches
Body Diameter:
Between 1.057 inches and 1.067 inches
Shaft Diameter:
Between 0.1246 inches and 0.1249 inches
Shaft Length:
Between 0.450 inches and 0.490 inches
Body Length:
Between 0.540 inches and 0.550 inches
Mounting Lip Diameter:
Between 1.0570 inches and 1.0670 inches
Mounting Lip Depth:
Between 0.0570 inches and 0.0670 inches
Shaft Style:
Round, slotted
Shaft Bearing Type:
Bearing
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
336.0
Maximum Starting Torque:
1.00 inch-ounces
Maximum Running Torque:
1.00 inch-ounces

At 9 oclock

Nonturn Device Radius:

Nonturn Device Location:

0.400 inches

NSN 5905-00-533-6271

Precision Nonwire Wound Variable Resistor - Page 2 of 2



Shott End Blow
Shaft End Play:
0.004 inches
Fragility Factor:
Moderately rugged
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Clamp ring
Electrical Resistance Per Section:
5.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
360.0
Resistance Tempurature Characteristic Range Per Section In Percent:
-5.0/+5.0 25 degrees celsius single section
Function Conformity Tolerance Per Section:
-1.00/+1.00 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 single section
Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Function Conformity Per Section:
Single section absolute linearity
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Actuator Travel Control Feature:
Continuous motion
Function Characteristic Per Section:
Single section linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Terminal Type And Quantity:
3 turret
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0