NSN 5905-00-533-6272

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-533-6272

Section Quantity:
1
Reliability Indicator:
Not established
Shaft Diameter:
0.1249 inches
Shaft Length:
0.620 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
328.0
Maximum Starting Torque:
0.50 inch-ounces
Maximum Running Torque:
0.50 inch-ounces
Shaft End Play:
0.004 inches
Screw Thread Diameter:
0.086 inches
Screw Thread Series Designator:
Unc
Screw Thready Qty Per Inch (tpi):
56.0
Mounting Facility Quantity:
2
Terminal Location:
Rear end
Mounting Method:
Threaded hole and clamp ring
Electrical Resistance Per Section:
5.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
360.0
Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Resistance Tolerance Per Section In Percent:
-1.0/+1.0 single section
Actuator Travel Control Feature:

Continuous motion

NSN 5905-00-533-6272

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Terminal Type And Quantity:
3 turret
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fila:

A002a0