Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-534-4807

# Section Quantity:

1

Body Style:

Rectangular w/mounting holes

# Reliability Indicator:

Not established

#### **Overall Length:**

0.470 inches

#### **Terminal Length:**

6.000 inches

#### **Overall Height:**

0.375 inches

#### **Overall Width:**

0.150 inches

#### Mounting Hole Diameter:

# 0.072 inches

Shaft Diameter:

0.075 inches

## Shaft Length:

0.080 inches

# Body Length:

0.375 inches

#### **Body Width:**

0.150 inches

#### **Body Height:**

0.375 inches

#### Shaft Style:

Round, slotted

#### Actuator Type:

Single shaft

# Lateral Distance Between Mounting Hole Centers:

0.419 inches

# Mounting Facility Quantity:

2

```
Terminal Location:
```

Rear end

#### Mounting Method:

Unthreaded hole

#### **Electrical Resistance Per Section:**

1.000 kilohms single section

## Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

# NSN 5905-00-534-4807

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-50.0 to 50.0 single section

## Power Dissipation Rating Per Section In Watts:

0.75 free air single section

**Resistance Tolerance Per Section In Percent:** 

-5.0 to 5.0 single section

## Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

85.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 wire lead

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0