Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-534-6454

### Section Quantity:

1

Body Style:

Rectangular

### **Reliability Indicator:**

Not established

#### Terminal Length:

0.300 inches

#### Shaft Diameter:

0.075 inches

#### Shaft Length:

0.080 inches

#### Body Length:

0.420 inches

#### Body Width:

0.190 inches

## Body Height:

0.375 inches

# Shaft Style:

Round, slotted

### Actuator Type:

Single shaft

#### Center To Center Distance Between Terminals:

0.200 inches

#### **Terminal Location:**

Lower adjacent side single row

#### **Mounting Method:**

Terminal

#### **Electrical Resistance Per Section:**

100.0 ohms single section

#### Center To Center Distance Between Center Terminal And Outside Terminal:

0.100 inches

### Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

### Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-250.0 to 250.0 single section

### Power Dissipation Rating Per Section In Watts:

0.5 free air single section

### **Resistance Tolerance Per Section In Percent:**

-10.0 to 10.0 single section

## Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

85.0 single section

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Standard Taper Curve Per Section:

A single section

### Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

### Unit Of Measure:

---

### Demilitarization:

No

Fiig:

A002a0