

View Online at <https://aerobasegroup.com/nsn/5905-00-535-9352>

**Section Quantity:**

2

**Body Style:**

Cylindrical bushing mounted

**Reliability Indicator:**

Not established

**Overall Length:**

2.219 inches

**Body Diameter:**

Between 1.047 inches and 1.078 inches

**Shaft Diameter:**

Between 0.124 inches and 0.125 inches

**Shaft Length:**

Between 0.969 inches and 1.031 inches

**Mounting Bushing Length:**

Between 0.547 inches and 0.578 inches

**Body Length:**

1.188 inches

**Overall Diameter:**

1.579 inches

**Shaft Style:**

Round, slotted

**Actuator Type:**

Single shaft

**Effective Electrical Rotation In Deg Angular Rotation:**

320.0

**Nonturn Device Location:**

At 12 oclock

**Nonturn Device Radius:**

Between 0.297 inches and 0.328 inches

**Screw Thread Diameter:**

0.250 inches

**Screw Thread Series Designator:**

Unf

**Screw Thread Qty Per Inch (tpi):**

28.0

**Terminal Location:**

Radially positioned over less than half the circumference

**Mounting Method:**

Locking bushing

**Features Provided:**

Nonmetallic shaft

**Electrical Resistance Per Section:**

10.000 kilohms 2nd section

**Rotary Actuator Travel In Angular Deg:**

332.0

**Power Dissipation Rating Per Section In Watts:**

2.0 free air all sections

**Resistance Tolerance Per Section In Percent:**

-2.0 to 2.0 all sections

**Actuator Travel Control Feature:**

Stops

**Standard Taper Curve Per Section:**

A all sections

**Terminal Type And Quantity:**

6 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A002a0