

View Online at <https://aerobasegroup.com/nsn/5905-00-535-9353>

Section Quantity:

2

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Body Diameter:

1.250 inches

Shaft Diameter:

Between 0.124 inches and 0.125 inches

Shaft Length:

1.000 inches

Mounting Bushing Length:

0.563 inches

Body Length:

1.188 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

320.0

Nonturn Device Location:

At 12 oclock

Nonturn Device Radius:

0.312 inches

Screw Thread Diameter:

0.250 inches

Screw Thread Series Designator:

Unf

Screw Thready Qty Per Inch (tpi):

28.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Locking bushing

Electrical Resistance Per Section:

5.000 kilohms 2nd section

Rotary Actuator Travel In Angular Deg:

332.0

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

145.0 all sections

Power Dissipation Rating Per Section In Watts:

2.0 free air all sections

Resistance Tolerance Per Section In Percent:

-2.0 to 2.0 all sections

Actuator Travel Control Feature:

Stops

Standard Taper Curve Per Section:

A all sections

Terminal Type And Quantity:

6 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0