

View Online at <https://aerobasegroup.com/nsn/5905-00-535-9364>

Section Quantity:

1

Body Style:

Rectilinear, slide control

Reliability Indicator:

Not established

Mounting Slot Width:

0.218 inches

Shaft Diameter:

0.250 inches

Shaft Length:

0.561 inches

Body Length:

4.062 inches

Body Width:

0.875 inches

Body Height:

1.750 inches

Undercut Diameter:

0.126 inches

Shaft Style:

Round, stepped

Actuator Type:

Single shaft

Longitudinal Actuator Travel:

2.850 inches

Longitudinal Actuator Effective Electrical Stroke Length:

2.850 inches

Fragility Factor:

Moderately rugged

Undercut Length:

0.155 inches

Mounting Facility Quantity:

2

Terminal Location:

Rear end

Mounting Method:

Slot

Features Provided:

Humidity proof

Electrical Resistance Per Section:

41.0 percent, rated amperes c and better flooring

Function Conformity Tolerance Per Section:

-1.00/+1.00 single section

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

71.0 single section

Power Dissipation Rating Per Section In Watts:

0.25 7th secondary quality

Function Conformity Per Section:

Single section independent linearity

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

Actuator Travel Control Feature:

Stops

Function Characteristic Per Section:

7 oclock all primaries

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

20.0 single section

Test Data Document:

88277-8524695 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

1 connector, receptacle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0