## NSN 5905-00-535-9955

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-535-9955 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 1.490 inches **Body Diameter:** 0.875 inches **Shaft Diameter:** 0.2497 inches **Shaft Length:** 0.812 inches **Mounting Bushing Length:** 0.312 inches **Body Length:** 0.678 inches **Overall Diameter:** 1.063 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 1800.0 **Maximum Starting Torque:** 0.60 inch-ounces **Maximum Running Torque:** 0.60 inch-ounces **Nonturn Device Location:** At 9 oclock **Nonturn Device Radius:** 0.290 inches **Shaft End Play:** 0.00500 inches **Shaft Runout:** 0.002 inches **Shaft Radial Play:** 

0.002 inchesScrew Thread Diameter:0.375 inches

## NSN 5905-00-535-9955

No

Precision Wire Wound Variable Resistor - Page 2 of 3



Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Features Provided:
Humidity proof
Electrical Resistance Per Section:
10.000 kilohms single section
Rotary Actuator Travel In Angular Deg:
1800.0
Function Conformity Tolerance Per Section:
-0.30/+0.30 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Power Dissipation Rating Per Section In Watts:
1.5 free air single section
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-3.0/+3.0 single section
Actuator Travel Control Feature:
Stops
Function Characteristic Per Section:
Single section linear
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
-20.0/+20.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Precious Material And Location:
Terminals gold
Precious Material:
Gold
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

## NSN 5905-00-535-9955

Precision Wire Wound Variable Resistor - Page 3 of 3



Fiig:

A002a0