Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-539-1216

# Section Quantity:

1

Body Style:

Cylindrical tab/flange mounted

# **Reliability Indicator:**

Not established

### **Body Diameter:**

0.750 inches

#### Mounting Hole Diameter:

Between 0.130 inches and 0.135 inches

### **Body Length:**

0.375 inches

Actuator Type:

#### Flush drive with slot-hole

# Effective Electrical Rotation In Deg Angular Rotation:

220.0

# Maximum Starting Torque:

10.00 inch-ounces

### Maximum Running Torque:

10.00 inch-ounces

### Maximum Stop Torque:

48.00 inch-ounces

# Lateral Distance Between Mounting Hole Centers:

1.000 inches

# **Mounting Facility Quantity:**

2

# **Terminal Location:**

Radially positioned over more than half the circumference

#### **Mounting Method:**

Unthreaded hole

#### **Electrical Resistance Per Section:**

100.0 ohms single section

# **Rotary Actuator Travel In Angular Deg:**

220.0

# Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

105.0 single section

# Power Dissipation Rating Per Section In Watts:

2.0 free air single section

# **Resistance Tolerance Per Section In Percent:**

-20.0 to 20.0 single section

# Actuator Travel Control Feature:

Stops



### Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

### Standard Taper Curve Per Section:

A single section

# Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

---

# Demilitarization:

No

### Fiig:

A002a0