NSN 5905-00-539-2994

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-539-2994

Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Body Diameter:
Between 0.484 inches and 0.516 inches
Shaft Diameter:
Between 0.122 inches and 0.126 inches
Shaft Length:
Between 0.844 inches and 0.906 inches
Mounting Bushing Length:
Between 0.234 inches and 0.266 inches
Body Length:
Between 0.437 inches and 0.469 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Maximum Starting Torque:
6.00 inch-ounces
6.00 inch-ounces Maximum Stop Torque:
Maximum Stop Torque:
Maximum Stop Torque: 48.00 inch-ounces
Maximum Stop Torque: 48.00 inch-ounces Nonturn Device Radius:
Maximum Stop Torque: 48.00 inch-ounces Nonturn Device Radius: Between 0.240 inches and 0.250 inches
Maximum Stop Torque: 48.00 inch-ounces Nonturn Device Radius: Between 0.240 inches and 0.250 inches Screw Thread Diameter:
Maximum Stop Torque: 48.00 inch-ounces Nonturn Device Radius: Between 0.240 inches and 0.250 inches Screw Thread Diameter: 0.250 inches
Maximum Stop Torque: 48.00 inch-ounces Nonturn Device Radius: Between 0.240 inches and 0.250 inches Screw Thread Diameter: 0.250 inches Screw Thread Series Designator:
Maximum Stop Torque: 48.00 inch-ounces Nonturn Device Radius: Between 0.240 inches and 0.250 inches Screw Thread Diameter: 0.250 inches Screw Thread Series Designator: Unef
Maximum Stop Torque: 48.00 inch-ounces Nonturn Device Radius: Between 0.240 inches and 0.250 inches Screw Thread Diameter: 0.250 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi):
Maximum Stop Torque: 48.00 inch-ounces Nonturn Device Radius: Between 0.240 inches and 0.250 inches Screw Thread Diameter: 0.250 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0
Maximum Stop Torque: 48.00 inch-ounces Nonturn Device Radius: Between 0.240 inches and 0.250 inches Screw Thread Diameter: 0.250 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location:
Maximum Stop Torque: 48.00 inch-ounces Nonturn Device Radius: Between 0.240 inches and 0.250 inches Screw Thread Diameter: 0.250 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location: Rear end
Maximum Stop Torque: 48.00 inch-ounces Nonturn Device Radius: Between 0.240 inches and 0.250 inches Screw Thread Diameter: 0.250 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location: Rear end Mounting Method:
Maximum Stop Torque: 48.00 inch-ounces Nonturn Device Radius: Between 0.240 inches and 0.250 inches Screw Thread Diameter: 0.250 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location: Rear end Mounting Method: Standard bushing
Maximum Stop Torque: 48.00 inch-ounces Nonturn Device Radius: Between 0.240 inches and 0.250 inches Screw Thread Diameter: 0.250 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location: Rear end Mounting Method: Standard bushing Electrical Resistance Per Section:

120.0 single section

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

NSN 5905-00-539-2994

No Fiig: A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Power Dissipation Rating Per Section In Watts:
0.5 free air single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Test Data Document:
81349-mil-r-94 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
3 tab, solder lug
Specification Data:
81349-mil-r-94/3 government specification
Shelf Life:
N/a
Unit Of Measure:

Demilitarization: