NSN 5905-00-539-4259

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-539-4259

Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Overall Length:
2.250 inches
Body Diameter:
1.120 inches
Shaft Diameter:
Between 0.249 inches and 0.252 inches
Shaft Length:
1.625 inches
Mounting Bushing Length:
0.375 inches
Body Length:
0.625 inches
Overall Diameter:
1.782 inches
Shaft Style:
Round
Actuator Type:
Single shaft
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over more than half the circumference
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
1.5 kilohms single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Fixed Tap Quantity Per Section:

Resistance Tolerance Per Section In Percent: -10.0 to 10.0 single section

1 single section

NSN 5905-00-539-4259

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Tap Location From Ccw Terminal Per Section In Ohms
--

750.0 single section

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

4 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0