NSN 5905-00-539-4897



View Online at https://aerob	asegroup.com/nsn/5905-00-539-4897
Section Quantity:	
1	
Body Style:	
Cylindrical bushing mounted	l
Reliability Indicator:	
Not established	
Overall Length:	
Between 1.062 inches and	.312 inches
Body Diameter:	
Between 1.032 inches and	.156 inches
Shaft Diameter:	
Between 0.248 inches and 0	0.251 inches
Shaft Length:	
Between 0.594 inches and 0	0.656 inches
Mounting Bushing Length	:
Between 0.485 inches and 0	0.515 inches
Body Length:	
Between 0.468 inches and 0	0.656 inches
Overall Diameter:	
1.515 inches	
Shaft Style:	
Round, slotted	
Actuator Type:	
Single shaft	
Maximum Starting Torque	:
6.00 inch-ounces	
Maximum Stop Torque:	
128.00 inch-ounces	
Nonturn Device Location:	

Nonturn Device Location:

At 9 oclock

Nonturn Device Radius:

Between 0.515 inches and 0.547 inches

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Locking bushing

NSN 5905-00-539-4897

A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Electrical Resistance Per Section:
500.0 ohms single section
Rotary Actuator Travel In Angular Deg:
Between 309.0 and 320.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
120.0 single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Test Data Document:
81349-mil-r-94 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification formation
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
3 tab, solder lug
Specification Data:
81349-mil-r-94/5 government specification
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig: