NSN 5905-00-539-5017

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View	Online at https://aerobasegroup.com/nsn/5905-00-539-5017
Section	on Quantity:
1	
Body	Style:
Cylind	drical bushing mounted
Relial	bility Indicator:
Not es	stablished
Overa	all Length:
Betwe	een 1.203 inches and 1.297 inches
Body	Diameter:
Betwe	een 0.719 inches and 0.781 inches
Shaft	Diameter:
Betwe	een 0.124 inches and 0.126 inches
Shaft	Length:
Betwe	een 0.844 inches and 0.906 inches
Moun	ting Bushing Length:
Betwe	een 0.234 inches and 0.266 inches
Body	Length:
Betwe	een 0.359 inches and 0.391 inches
Overa	all Diameter:
0.953	inches
Shaft	Style:
Round	d, slotted
Actua	ator Type:
Single	shaft
Maxin	num Starting Torque:
6.00 iı	nch-ounces
Maxin	num Stop Torque:
80.00	inch-ounces
Nontu	ırn Device Location:
At 9 o	clock
Nontu	ırn Device Radius:
Betwe	een 0.359 inches and 0.391 inches
Screv	v Thread Diameter:

0.250 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

NSN 5905-00-539-5017

Fiig: A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Electrical Resistance Per Section:
5.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
Between 295.0 and 305.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
120.0 single section
Power Dissipation Rating Per Section In Watts:
0.5 free air single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Test Data Document:
81349-mil-r-94 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification formation
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
3 tab, solder lug
Specification Data:
81349-mil-r-94/2 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No