

View Online at <https://aerobasegroup.com/nsn/5905-00-542-2017>

Section Quantity:

1

Body Style:

Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

Between 0.7807 inches and 0.7821 inches

Pilot Length:

0.0620 inches

Overall Length:

1.072 inches

Undercut Diameter:

0.781 inches

Undercut Width:

0.0620 inches

Body Diameter:

0.875 inches

Shaft Diameter:

Between 0.1246 inches and 0.1249 inches

Shaft Length:

Between 0.390 inches and 0.422 inches

Body Length:

0.650 inches

Mounting Lip Diameter:

0.8750 inches

Mounting Lip Depth:

0.0620 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Clamp ring

Electrical Resistance Per Section:

20.000 kilohms single section

Power Dissipation Rating Per Section In Watts:

0.5 free air single section

Fixed Tap Quantity Per Section:

1 single section

Resistance Tolerance Per Section In Percent:

-5.0 to 5.0 single section

Tap Location From Ccw Terminal Per Section In Ohms:

10000.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

4 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A002a0