## NSN 5905-00-542-7774

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-542-7774 **Section Quantity:** 1 **Body Style:** Rectangular w/mounting holes/slots **Reliability Indicator:** Not established **Overall Height:** 0.312 inches **Overall Width:** 0.250 inches **Mounting Hole Diameter:** 0.086 inches **Shaft Diameter:** 0.125 inches **Shaft Length:** 0.062 inches **Body Length:** 1.250 inches **Body Width:** 0.250 inches **Body Height:** 0.312 inches **Mounting Hole/stud Circle Diameter:** 0.086 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Distance Between Mounting Hole Centers:** 1.000 inches **Lateral Distance Between Mounting Hole Centers:** 1.000 inches **Mounting Facility Quantity:** 2 **Terminal Location:** Rear end **Mounting Method:** Unthreaded hole

**Electrical Resistance Per Section:** 5.000 kilohms single section

**Power Dissipation Rating Per Section In Watts:** 

1.0 free air single section

## NSN 5905-00-542-7774

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



R	esistance	<b>Tolerance</b>	Per 9	Section	In	Percent:
◥	esisiance	i olei alice	rei .	Section		reiteiit.

-10.0 to 10.0 single section

**Standard Taper Curve Per Section:** 

A single section

**Terminal Type And Quantity:** 

3 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

Demilitarization:

No

Fiig:

A002a0