NSN 5905-00-542-8046



| View Online at https://aerobase | group.com/nsn/5905-00-542-8046 |
|---------------------------------|--------------------------------|
| Section Quantity: | |
| 1 | |
| Body Style: | |
| Cylindrical bushing mounted | |
| Reliability Indicator: | |
| Not established | |
| Overall Length: | |
| Between 0.937 inches and 1.18 | 37 inches |
| Body Diameter: | |
| Between 1.032 inches and 1.15 | 66 inches |
| Shaft Diameter: | |
| Between 0.248 inches and 0.25 | 51 inches |
| Shaft Length: | |
| Between 0.469 inches and 0.53 | 31 inches |
| Mounting Bushing Length: | |
| Between 0.344 inches and 0.39 | 00 inches |
| Body Length: | |
| Between 0.468 inches and 0.65 | 66 inches |
| Overall Diameter: | |
| 1.515 inches | |
| Shaft Style: | |
| Round, slotted | |
| Actuator Type: | |
| Single shaft | |
| Maximum Starting Torque: | |
| 6.00 inch-ounces | |
| Maximum Stop Torque: | |
| 128 00 inch ounces | |

128.00 inch-ounces

Nonturn Device Location:

At 9 oclock

Nonturn Device Radius:

Between 0.515 inches and 0.547 inches

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

NSN 5905-00-542-8046

Fiig: A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



| Electrical Resistance Per Section: |
|---|
| 1.0 kilohms single section |
| Rotary Actuator Travel In Angular Deg: |
| Between 309.0 and 320.0 |
| Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: |
| 120.0 single section |
| Power Dissipation Rating Per Section In Watts: |
| 2.0 free air single section |
| Resistance Tolerance Per Section In Percent: |
| 10.0 to 10.0 single section |
| Actuator Travel Control Feature: |
| Stops |
| Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: |
| 70.0 single section |
| Standard Taper Curve Per Section: |
| A single section |
| Test Data Document: |
| 31349-mil-r-94 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification forma |
| excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental |
| and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Terminal Type And Quantity: |
| 3 tab, solder lug |
| Specification Data: |
| 31349-mil-r-94/5 government specification |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| - |
| Demilitarization: |
| No |