## NSN 5905-00-542-8048



| Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2    | - |
|---|---|
| View Online at https://aerobasegroup.com/nsn/5905-00-542-8048 |   |
| Section Quantity:   |   |
| 1   |   |
| Body Style:   |   |
| Cylindrical bushing mounted                                   |   |
| Reliability Indicator:  |   |
| Not established   |   |
| Overall Length:   |   |
| Between 0.937 inches and 1.187 inches                         |   |
| Body Diameter:  |   |
| Between 1.032 inches and 1.156 inches                         |   |
| Shaft Diameter:   |   |
| Between 0.248 inches and 0.251 inches                         |   |
| Shaft Length:   |   |
| Between 0.469 inches and 0.531 inches                         |   |
| Mounting Bushing Length:                                      |   |
| Between 0.344 inches and 0.390 inches                         |   |
| Body Length:  |   |
| Between 0.468 inches and 0.656 inches                         |   |
| Overall Diameter:   |   |
| 1.515 inches  |   |
| Shaft Style:  |   |
| Round, slotted  |   |
| Actuator Type:  |   |
| Single shaft  |   |
| Maximum Starting Torque:                                      |   |
| 6.00 inch-ounces  |   |
| Maximum Stop Torque:  |   |
| 128.00 inch-ounces  |   |
| Nonturn Device Location:                                      |   |
|   |   |

At 9 oclock

**Nonturn Device Radius:** 

Between 0.515 inches and 0.547 inches

**Screw Thread Diameter:** 

0.375 inches

**Screw Thread Series Designator:** 

Unef

Screw Thready Qty Per Inch (tpi):

32.0

**Terminal Location:** 

Radially positioned over less than half the circumference

**Mounting Method:** 

Standard bushing

## NSN 5905-00-542-8048

A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



| Electrical Resistance Per Section:  |
|---|
| 100.0 kilohms single section  |
| Rotary Actuator Travel In Angular Deg:  |
| Between 309.0 and 320.0   |
| Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:   |
| 120.0 single section  |
| Power Dissipation Rating Per Section In Watts:  |
| 2.0 free air single section   |
| Resistance Tolerance Per Section In Percent:  |
| -10.0 to 10.0 single section  |
| Actuator Travel Control Feature:  |
| Stops   |
| Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:   |
| 70.0 single section   |
| Standard Taper Curve Per Section:   |
| A single section  |
| Test Data Document:   |
| 81349-mil-r-94 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; |
| excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental         |
| and performance requirements and test conditions that are shown as "typical", "average", "", etc.).   |
| Terminal Type And Quantity:   |
| 3 tab, solder lug   |
| Specification Data:   |
| 81349-mil-r-94/5 government specification   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |
| Fiig:   |