Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-542-8933

# Section Quantity:

1

Body Style:

Cylindrical bushing mounted

# **Reliability Indicator:**

Not established

## **Body Diameter:**

1.156 inches

#### Shaft Diameter:

0.250 inches

#### Shaft Length:

0.500 inches

## Mounting Bushing Length:

0.375 inches

## Body Length:

## 0.625 inches

Shaft Style:

Round, slotted

## Actuator Type:

Single shaft

## Effective Electrical Rotation In Deg Angular Rotation:

312.0

## Nonturn Device Location:

At 9 oclock

## Nonturn Device Radius:

0.531 inches

#### Screw Thread Diameter:

0.375 inches

## Screw Thread Series Designator:

Unef

# Screw Thready Qty Per Inch (tpi):

32.0

# **Terminal Location:**

Radially positioned over less than half the circumference

# Mounting Method:

Standard bushing

# **Electrical Resistance Per Section:**

10.0 megohms single section

# Rotary Actuator Travel In Angular Deg:

312.0

# Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

120.0 single section

# NSN 5905-00-542-8933 Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Power Dissipation Rating Per Section In Watts:

2.0 free air single section

## **Resistance Tolerance Per Section In Percent:**

-20.0 to 20.0 single section

# Actuator Travel Control Feature:

Stops

## Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

## Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

#### Unit Of Measure:

--

# Demilitarization:

No

## Fiig:

A002a0