NSN 5905-00-542-9316



View Onli	ine at https://aerobasegroup.com/nsn/5905-00-542-9316
Section (Quantity:
1	
Body Sty	rle:
Cylindrica	al bushing mounted
Reliabilit	y Indicator:
Not estab	blished
Overall L	ength:
Between	0.947 inches and 1.187 inches
Body Dia	ameter:
Between	1.032 inches and 1.156 inches
Shaft Dia	ameter:
Between	0.248 inches and 0.251 inches
Shaft Lei	ngth:
Between	2.469 inches and 2.531 inches
Mounting	g Bushing Length:
Between	0.344 inches and 0.390 inches
Body Le	ngth:
Between	0.478 inches and 0.656 inches
Overall D	Diameter:
1.515 inc	hes
Shaft Sty	rle:
Round, s	slotted
Actuator	Type:
Single sh	aft
Maximun	n Starting Torque:
6.00 inch	-ounces
Maximun	n Stop Torque:
128 NN in	ch-ounces

Nonturn Device Location:

At 9 oclock

Nonturn Device Radius:

Between 0.515 inches and 0.547 inches

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

NSN 5905-00-542-9316

A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Electrical Resistance Per Section:
5.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
Between 309.0 and 320.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
120.0 single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Test Data Document:
81349-mil-r-94 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification forma
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
3 tab, solder lug
Specification Data:
81349-mil-r-94/5 government specification
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiia: