NSN 5905-00-542-9664

Inductive Wire Wound Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-542-9664

Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:				
-26.0/+26.0				
Electrical Resistance:				
5.000 kilohms				
Resistance Tolerance In Percent:				
-3.000/+3.000				
Heat Sink Material:				
Aluminum alloy				
Heat Sink Length:				
7.000 inches				
Heat Sink Width:				
5.000 inches				
Heat Sink Height:				
2.000 inches				
Heat Sink Thickness:				
0.040 inches				
Ambient Tempurature In Deg Celsius At Full Rated Power:				
40.0				
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:				
275.0				
Tempurature Range Of Tempurature Coefficient In Deg Celsius:				
-55.0/+275.0				
Inclosure Method:				
Encased				
Terminal Type:				
Tab, solder lug				
Terminal Length:				
0.406 inches				
Body Length:				
1.969 inches				
Body Width:				
0.625 inches				
Body Height:				
0.625 inches				
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:				
1.562 inches				
Power Dissipation Rating In Watts:				
30.000 free air				
Terminal Width:				
0.140 inches				
Mounting Hole Size:				

0.125 inches

NSN 5905-00-542-9664

Inductive Wire Wound Fixed Resistor - Page 2 of 2



~ .			
Stvie	e Des	sıan	ator:

Axial terminal (s)

Test Data Document:

81349-mil-r-18546 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-r-18546b/ships/superseded/ government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A001a0