## NSN 5905-00-542-9981



1	Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2
١	/iew Online at https://aerobasegroup.com/nsn/5905-00-542-9981
5	Section Quantity:
1	
E	Body Style:
(	Cylindrical bushing mounted
F	Reliability Indicator:
١	Not established
(	Overall Length:
E	Between 1.312 inches and 1.562 inches
E	Body Diameter:
E	Between 1.032 inches and 1.156 inches
5	Shaft Diameter:
E	Between 0.248 inches and 0.251 inches
5	Shaft Length:
E	Between 0.844 inches and 0.906 inches
N	Mounting Bushing Length:
E	Between 0.485 inches and 0.515 inches
E	Body Length:
E	Between 0.468 inches and 0.656 inches
C	Overall Diameter:
1	.515 inches
5	Shaft Style:
F	Round, slotted
A	Actuator Type:
5	Single shaft
N	Maximum Starting Torque:
6	5.00 inch-ounces
N	Maximum Stop Torque:
1	28.00 inch-ounces
	Jonturn Device Location:

**Nonturn Device Location:** 

At 9 oclock

**Nonturn Device Radius:** 

Between 0.515 inches and 0.547 inches

**Screw Thread Diameter:** 

0.375 inches

**Screw Thread Series Designator:** 

Unef

Screw Thready Qty Per Inch (tpi):

32.0

**Terminal Location:** 

Radially positioned over less than half the circumference

**Mounting Method:** 

Standard bushing

## NSN 5905-00-542-9981

**Fiig:** A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Electrical Resistance Per Section:
5.0 megohms single section
Rotary Actuator Travel In Angular Deg:
Between 309.0 and 320.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
120.0 single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Test Data Document:
81349-mil-r-94 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
3 tab, solder lug
Specification Data:
81349-mil-r-94/5 government specification
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No