Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-543-0459

# Section Quantity:

1

Body Style:

Rectangular

## **Reliability Indicator:**

Not established

#### **Terminal Length:**

0.188 inches

#### Shaft Diameter:

0.090 inches

#### Shaft Length:

0.062 inches

#### **Body Length:**

0.375 inches

#### Body Width:

0.200 inches

# Body Height:

0.410 inches

# Shaft Style:

Round, slotted

# Actuator Type:

Single shaft

#### Effective Electrical Rotation In Deg Angular Rotation:

7200.0

#### **Center To Center Distance Between Terminals:**

0.200 inches

#### **Terminal Location:**

Upper adjacent side single row

#### **Mounting Method:**

Terminal

#### **Electrical Resistance Per Section:**

20.0 kilohms single section

#### Center To Center Distance Between Center Terminal And Outside Terminal:

0.100 inches

#### Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

105.0 single section

#### Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-100.0 to 100.0 single section

### Power Dissipation Rating Per Section In Watts:

0.5 free air single section

#### **Resistance Tolerance Per Section In Percent:**

-10.0 to 10.0 single section

# NSN 5905-00-543-0459

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



**Actuator Travel Control Feature:** 

Clutch

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

25.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0