NSN 5905-00-543-8348

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-543-8348

Electrical Resistance: 154.000 ohms Resistance Tolerance In Percent: 1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 150.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 1.002 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document:
Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method:
Resistance Tolerance In Percent: 1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 150.0/+150.0 Inclosure Method: Incapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 1.062 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document:
Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 150.0/+150.0 Inclosure Method: Incapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 1.062 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Avial terminal each end Test Data Document:
Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 1.062 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 1.062 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 1.062 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document:
If Empurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+150.0 Inclosure Method: Incapsulated If Emminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 1.062 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end If Est Data Document:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 10.375 inches Body Length: 1.062 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document:
Inclosure Method: Inclosure Me
Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 1.062 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Fest Data Document:
Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 1.062 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Fest Data Document:
Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 1.062 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document:
Wire lead Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 1.062 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document:
Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 1.062 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document:
Not established Body Diameter: 0.375 inches Body Length: 1.062 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document:
Body Diameter: 0.375 inches Body Length: 1.062 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document:
D.375 inches Body Length: 1.062 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Fest Data Document:
Body Length: 1.062 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document:
1.062 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document:
Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document:
1.000 free air Style Designator: Axial terminal each end Test Data Document:
Style Designator: Axial terminal each end Test Data Document:
Axial terminal each end Test Data Document:
Test Data Document:
31349-mil-r-10509 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
31349-mil-r-10509/5 government specification
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Filg:
A001a0